

AMENDMENTS TO THE CLAIMS

Please amend claims 1, 2, 6, 7, 11, 15, 16, 20, 21 and 25, and cancel claims 12 and 26.

This listing of claims will replace all prior versions, and listings, of claims in the application:

CLAIMS

What is claimed is:

1 1. (Currently Amended) A robot system, comprising:
2 a remote station that has a camera that captures a remote station image;
3 a mobile robot that is controlled by said remote station and has a monitor that
4 displays the remote station image, and a camera that captures a robot image, said monitor
5 and said camera move together in at least one degree of freedom; and,
6 a head worn device, said head worn device generates input signals in response to
7 movement of said head worn device, said robot camera moves in conjunction with the
8 movement of said head worn device, said head worn device displays said robot images.

1 2. (Currently Amended) The system of claim 1, wherein said mobile robot
2 includes a holonomic mobile platform.

1 3. (Previously Presented) The system of claim 1, wherein said head worn
2 device displays graphics.

1 4. (Original) The system of claim 1, wherein said head worn device includes a
2 microphone.

1 5. (Original) The system of claim 4, wherein said remote station includes a
2 speech interface that interprets robot commands entered through said microphone.

1 6. (Currently Amended) A robot system, comprising:
2 a remote station with a camera that captures a remote station image;
3 a mobile robot that is controlled by said remote station and has a monitor that
4 displays the remote station image and a camera captures a robot image, said monitor and
5 said camera move together in at least one degree of freedom; and,
6 head worn means for moving said robot camera in conjunction with movement of a
7 user's head and displaying the robot images.

1 7. (Currently Amended) The system of claim 6, wherein said mobile robot
2 includes a holonomic mobile platform.

1 8. (Previously Presented) The system of claim 6, wherein said head worn
2 device means displays graphics.

1 9. (Original) The system of claim 6, wherein said head worn means includes a
2 microphone.

1 10. (Original) The system of claim 9, wherein said remote station includes a
2 speech interface that interprets robot commands entered through said microphone.

1 11. (Currently Amended) A method for moving a camera of a robot,
2 comprising:
3 moving a head worn device;
4 generating input signals that correspond to the movement of the head worn device;
5 processing the input signals into a robot command;
6 transmitting the robot command to a robot;
7 moving together a monitor and a camera of the robot in response to the robot
8 command in at least one degree of freedom;
9 capturing a robot image with the robot camera;
10 capturing a remote station image with a remote station camera;
11 displaying the robot image with the head worn device; ~~and~~,
12 displaying the remote station image on [a]the monitor of the robot; and,
13 moving the robot across a surface.

1 12. (Canceled)

1 13. (Original) The method of claim 11, further comprising transmitting video
2 images between the robot and a remote station.

1 14. (Original) The method of claim 11, further comprising entering a robot
2 input command into a microphone of the head worn device and processing the robot input
3 command into a robot movement command, transmitting the robot movement command
4 to the robot, and moving the robot.

1 15. (Currently Amended) A robot system, comprising:

2 a broadband network;

3 a remote station that is coupled to said broadband network and has a camera that
4 captures a remote station image;

5 a mobile robot that is controlled by said remote station and coupled to said
6 broadband network and has a monitor that displays the remote station image, and a
7 camera that captures a robot image, said monitor and said camera move together in at
8 least one degree of freedom; and,

9 a head worn device, said head worn device generates input signals in response to
10 movement of said head worn device, said robot camera moves in conjunction with the
11 movement of said head worn device, said head worn device displays said robot images.

1 16. (Currently Amended) The system of claim 15, wherein said mobile robot
2 includes a holonomic mobile platform.

1 17. (Previously Presented) The system of claim 15, wherein said head worn
2 device displays graphics.

1 18. (Original) The system of claim 15, wherein said head worn device includes
2 a microphone.

1 19. (Original) The system of claim 18, wherein said remote station includes a
2 speech interface that interprets robot commands entered through said microphone.

1 20. (Currently Amended) A robot system, comprising:
2 a broadband network;
3 a remote station that is coupled to said broadband network, said remote station has
4 a camera that captures a remote station image;
5 a mobile robot that is controlled by said remote station and is coupled to said
6 broadband network and has a monitor that displays the remote station image, and a
7 camera that captures a robot image, said monitor and said camera move together in at
8 least one degree of freedom; and,
9 a head worn device means for moving said robot camera in conjunction with
10 movement of a user's head and displaying the robot images.

1 21. (Currently Amended) The system of claim 20, wherein said mobile robot
2 includes a holonomic mobile platform.

1 22. (Previously Presented) The system of claim 20, wherein said head worn
2 means displays graphics.

1 23. (Original) The system of claim 20, wherein said head worn means includes
2 a microphone.

1 24. (Original) The system of claim 23, wherein said remote station includes a
2 speech interface that interprets robot commands entered through said microphone.

1 25. (Currently Amended) A method for moving a camera of a robot,
2 comprising:
3 moving a head worn device;
4 generating input signals that correspond to the movement of the head worn device;
5 processing the input signals into a robot command;
6 transmitting the robot command to a robot through a broadband network;
7 moving together a monitor and a camera of the robot in response to the robot
8 command in at least one degree of freedom;
9 capturing a robot image with the robot camera;
10 capturing a remote station image with a remote station camera;
11 displaying the robot image with the head worn device; ~~and~~
12 displaying the remote station image on [a]the monitor of the robot; and,
13 moving the robot across a surface.

1 26. (Canceled)

1 27. (Original) The method of claim 25, further comprising transmitting video
2 images between the robot and a remote station.

1 28. (Original) The method of claim 27, further comprising entering a robot
2 input command into a microphone of the head worn device and processing the robot input
3 command into a robot movement command, transmitting the robot movement command
4 to the robot, and moving the robot.